



thinklogical®

A **BELDEN** BRAND

TLX MATRIX SWITCHES

SECURE SWITCHING SOLUTION

Thinklogical's TLX Matrix Switches are high performance, modular, non-blocking switches for complete, end-to-end switching over multi-mode or single mode fiber-optic cable.

TLX features real-time switching of DisplayPort and HDMI video, audio and peripheral signals. TLX Matrix Switches offer scalability, flexibility, security and resiliency for any size audio-visual application.

Information Assurance Certifications

Thinklogical's TLX line of switches has achieved IA certification to The Common Criteria EAL4, TEMPEST SDIP 27 Level B, NATO NIAPC Evaluation Scheme: GREEN status, and the U.S. DoD DISA JITC UCR APL 2013, distinguishing Thinklogical as a leader in mid-to-large scale fiber optic KVM and video matrix switches globally.

Thinklogical has met stringent information assurance directives for use in secure defense, intelligence, and infrastructure facilities worldwide. The TLX architecture enables the switching and distribution of multiple classification information through a single chassis, while maintaining network isolation. The innovative design reduces the need to air-gap systems to meet security requirements.

HIGH PERFORMANCE WITH SEAMLESS INTEGRATION

TLX Matrix Switches support uncompressed 10 Gbps bandwidth per port, preserving signal integrity to provide high resolution video with no artifacts, added latency, or lost frames. Thinklogical's patented reclocking technology ensures that every video and data stream is delivered in perfect synchronization.

TLX Switches are protocol agnostic, supporting all common video, audio, and peripheral signal interfaces and formats, ensuring seamless integration into any infrastructure. With TLX, users can consolidate signal switching requirements into a single chassis for enhanced productivity and reduced equipment maintenance and operational costs.

Switching systems may be configured with multi-mode or single mode fiber optics for increased flexibility in hybrid environments. Designed with completely non-blocking architectures, Thinklogical Matrix Switches offer the ability to configure each port on the switch as an input or an output and switch between all ports, maximizing system efficiency.

EXCEPTIONAL RELIABILITY, REDUNDANCY AND RESILIENCY

TLX Switches are designed to maximize system uptime for mission-critical applications. In addition to a mean time between failure (MTBF) of over 100,000 hours, the modular architecture of TLX Switches allow users to hot swap all critical system components. Power supplies, fan trays, control cards, input/output cards and pluggable optics are hot-swappable, to minimize system downtime in the unlikely event a component should fail.

Scalable from 12 to 1280 ports, TLX Matrix Switches are ideal for environments ranging from small conference rooms to large, complex command and control centers.

TLX24

MATRIX SWITCH

The TLX24 is a compact, high performance, non-blocking matrix switch for complete, end-to-end routing of video, audio and peripheral signals. **The 1RU Matrix may be configured as a unidirectional 24 x 24 or a bidirectional 12 x 12 switch.** The TLX24 incorporates a push button interface, for simplified access and control. All TLX Switches support uncompressed 10 Gbps bandwidth per port for low-latency signal management.

PRODUCT FEATURES

Configurable up to 24 x 24 switching
10 Gbps bandwidth per port
Reclocking technology maintains signal integrity
Protocol agnostic
Supports multi-mode & single mode fiber
Completely non-blocking architecture
Switch video and data up to 80 km
MTBF over 100,000 hours
Compatible with System Management Portfolio (SMP) for complete switch control and management
SNMP control protocol
Integrated web-based Administrative Interface (ADM)
Certifications to support secure installations
Optional push button front panel control interface

TLX24 SWITCH • FRONT PANEL



TLX24 SWITCH • BACK PANEL



ORDERING INFORMATION

PART NUMBER	DESCRIPTION
MATRIX SWITCH CHASSIS	
TLX-MSC-M00024	TLX24 Matrix Switch Chassis configured with 24 Multi-Mode Fiber Ports, Single Power Supply
TLX-MSC-S00024	TLX24 Matrix Switch Chassis with 24 Single Mode (10 km) Fiber Ports, Single Power Supply
SPARE MODULES	
TLX-MSM-P00024	TLX12 & TLX24 Power Supply

PRODUCT SPECIFICATIONS

OPTICAL DISTANCE	Multi-Mode: 400 m · 33 m (OM1); 82 m (OM2); 300 m (OM3); 400 m (OM4) · Single Mode: 80 km (OS2, 9/125)
OPTICAL DATA RATE	50 Mbps to 10 Gbps Per Port; Switching Capacity: 240 Gbps
ENVIRONMENTAL	Operating Temperature: 0 °C – 50 °C, Humidity: 5–95% RH, non-condensing
COMPLIANCE	Approvals for United States of America, Canada, and European Union
WARRANTY	One Year From Date of Shipment. Extended Warranties Available.
MOUNTING BRACKETS	19" Rack Mounting Brackets Included
POWER CONSUMPTION	75 W, 256 BTU/hr
SUPPLY VOLTAGE	Universal AC Power Supply, 100-240 VAC, 47-63 Hz
WEIGHT	12.0 lbs (5.4 kg) Fully Populated
DIMENSIONS	TOLERANCE ± 0.039" (1.00 MM)
RACK SIZE (WIDTH) HEIGHT x DEPTH	• EIA 19" (482.90 mm) • 1 RU 1.72" (43.69 mm) x 16.56" (420.50 mm)
SOFTWARE UPDATES	Console/LAN
FIRMWARE UPDATES	Mini USB Connector (1)
RS-232 SERIAL PORTS	DB9 Female Connectors (1)
1GbE NETWORK	RJ45 Connector (1)
CABLES INCLUDED	(1) AC Power Cable, (1) CAT5, 4.5 m (CBL000001-015FR), (1) USB 2.0 Type-A to Mini-B, 2 m (CBL000105-002MR)