

## Hybrid Switching Solution for Uncompressed, High Resolution Video & KVM Systems

Thinklogical's TLX Matrix Switches are *high performance, modular, non-blocking switches* for complete, end-to-end switching of video, audio and peripheral signals over multi-mode or single mode fiber optic cable or CATx cable. The bi-directional configuration capability adds simplicity and control over sophisticated video and KVM visual computing environments. TLX Matrix Switches offer scalability, flexibility, security and resiliency for any size switching application.

### Router Features

#### Highest Performance with Easiest Integration

TLX Matrix Switches support **10Gbps per port**, preserving signal integrity to provide uncompressed, high resolution video with no artifacts, latency or lost frames. Thinklogical's **re-clocking technology** ensures that every video and data stream is delivered in perfect synchronization. TLX Switches are protocol agnostic, supporting numerous video, audio and peripheral signals, allowing users to consolidate all of their system switching requirements into a single chassis. Switching systems may be configured with **multi-mode or single mode fiber and/or CATx connections**, for increased flexibility. Designed with **completely non-blocking architectures**, Thinklogical Switches offer the ability to switch between all ports, maximizing system efficiency. Additionally, each port on the switch may be configured as an input or an output. Scalable from **12 ports to 640 ports**, TLX Switches are ideal for small to large system applications.

#### Certified Security

##### Fiber-Based System

Fiber-based systems are inherently more secure than copper-based systems. Copper cabling presents security risks through electromagnetic interference, such as content sniffing and eavesdropping. Secure data transmitted over fiber optics cannot be compromised. Additionally, fiber extends content significantly greater distances than copper. Creating physical separation between

potential threats (users) and the target (secure data) is essential to a secure system design. Thinklogical's fiber-based system permits users to **access sources up to 80 kilometers away**, with no performance degradation. System administrators can safeguard sources in a centralized location, while users maintain remote access to the sources without the ability to accidentally or intentionally breach the system (such as downloading sensitive information onto a USB drive).

##### Partitioned and Restricted Switching

Thinklogical protects user's critical data, and **maintains information assurance between multiple networks**, through partitioned and restricted switching. Partitioning allows the router resources to be divided to support more than one network, and does not allow for switching between networks. Restricted switching allows the administrator to manage access on a port-by-port basis. Partitioned and restricted switching are enabled through the router's firmware, and therefore, a threat would have to physically access the router to tamper with the settings.

##### Accreditations

Thinklogical's VX line of switches are the only fiber optic KVM and Video Switches in the world that have achieved accreditation to **The Common Criteria EAL4, TEMPEST Level B, and NATO (National Information Assurance Partnership) Green Status**, having met stringent criteria that support information assurance directives for military-intelligence secure facilities worldwide. The TLX switches have been



designed to meet these specifications and are expected to achieve these, as well as additional, accreditations. Learn more at [www.thinklogical.com/accreditations](http://www.thinklogical.com/accreditations).

#### Exceptional Resiliency

TLX Switches are designed to maximize system uptime. In addition to a **Mean Time between Failure (MTBF) of over 100,000 hours**, the modular approach of the TLX Switches allow users to hot-swap all critical system components. **Power supplies, fan trays, control cards, input/output cards and pluggable optics are hot-swappable**, to minimize system downtime in the unlikely event a component should fail. Furthermore, the system can be easily reconfigured, such as adding additional input/output cards for expansion, without ever powering down the router or interrupting active signals. **Dual, redundant power supplies** ensure continuous, uninterrupted power to the router. Switches are also configurable to include **redundant control cards**. In the event the primary control card were to fail, the system will automatically failover to the redundant control card, with no delay or data loss. **Enhanced diagnostics and alarms** provide extensive real-time monitoring and diagnostics of the internal product operating temperature, power supply voltages, input and output fiber links, fans, and other critical functions of the router. Redundant control cards exhibit LED indicators to provide active and fault monitoring, while the system alarms can be configured to trigger an external control system, generate SNMP traps, or generate email notifications.

## TLX Matrix Switches · Product Features

ROUTER FEATURES		PORT CONFIGURATIONS						ROUTER SPECIFICATIONS						
Router Name		Data Card Port Count	Max Data Cards	Max Port Count	Uni-Directional Configuration up to	Bi-Directional Configuration up to	Input/Output at any Port	Automatic Tie-Line Reclocking	Height (Rack Units)	Redundant Power Supplies	Hot-Swappable Switch Cards	Common Criteria EAL4	TEMPEST Level B	NATO (NAIPC) Green
Compact, Non-Modular Switches														
TLX-12		12	1	12	12x12	6x6	✓	✓	1RU					
TLX-24		24	1	24	24x24	12x12	✓	✓	1RU					
Modular Switches														
TLX-48		16	3	48	48x48	24x24	✓	✓	3RU	✓		In Testing		
TLX-320		16	20	320	320x320	160x160	✓	✓	13RU	✓		In Testing		
TLX-640		20	32	640	640x640	320x320	✓	✓	28RU	✓	✓	In Testing		

### All Routers Feature

## Hot-Swappable Router Modules




- 10Gbps per Port
- Modular Switches include Modular and Hot-Swappable Components:
  - Control Cards
  - Data Input and Output Cards
  - Power Supplies
  - Fan Trays
  - Optical Modules
- Modular Switches Configurable to Include
  - Redundant Control Cards with Automatic Failover
  - Multi-Mode, Single Mode and CATxI Configurations
  - Compatibility with CWDM and DWDM Optical Modules
- Non-Blocking Architecture

## TLX24 MATRIX SWITCH


The TLX24 offers a compact, high performance, non-blocking matrix switch for complete, end-to-end routing of video and peripheral signals. The 1RU matrix is available in fiber, CATx and hybrid configurations and may be configured as a unidirectional 24x24 or a bidirectional 12x12 switch. Thinklogical's TLX24 incorporates a push button interface, for simplified access and control.




TLX24 Switch - Front



TLX24 Switch - Fiber Backpanel



TLX24 Switch - CATx Backpanel



TLX24 Switch - Hybrid Backpanel

### PRODUCT FEATURES

- Configurable up to a 24x24 switch
- 10Gbps bandwidth per port
- Re-clocking technology maintains signal integrity
- Protocol agnostic
- Multi-mode fiber, single mode fiber, CATx and hybrid configurations
- Completely non-blocking architecture
- Route video and data up to 80 kilometers
- MTBF over 100,000 hours
- Hot-swappable optical modules
- Replaceable modular power supply
- Push button control interface
- System Management Portfolio for complete switch control and management

### Specifications

Distance	CAT6a: 100m; Single Mode: 80km · OS2 (9/125) Multi-Mode 400m · 33m: OM1; 82m: OM2; 300m: OM3; 400m: OM4
Optical Wavelength	Multi-Mode: 850nm; Single Mode: 1310nm (CWDM/DWDM call)
Optical Data Rate	50Mbps to 10Gbps per port; Switching Capacity: 240Gbps
CATx Data Rate	10Gbps per port; Switching Capacity: 240Gbps
Environmental	Operating Temperature: 0°C-50°C Humidity: 5-95% RH, non-condensing
Compliance	Approvals for United States of America, Canada, and EU
Warranty	One year - Extended warranties available for purchase
Mounting Brackets	19" Rack Mounting Brackets Included
Power Consumption	200 Watts
Supply Voltage	Universal AC Power Supply, 100-240VAC, 47-63Hz
Weight	13lbs (5.90kg)
Dimensions [Tolerance ± 0.039" (1.00mm)]	
Rack Size (Width)	EIA 19" (482.90mm)
Height x Depth	1RU 1.72" (43.69mm) x 16.56" (420.50mm)
Software Updates	Console/LAN
Firmware Updates	Mini USB Connectors (1)
RS-232 Serial Ports	DB9 Female Connectors (1)
10/100 Network	RJ45 Connector (1)

### Ordering Information

Part Number	Description
<b>Matrix Switch Chassis</b>	
TLX-MSC-C00024	TLX24 Matrix Switch Chassis configured with 24 CATx Ports, Single Power Supply
TLX-MSC-M00024	TLX24 Matrix Switch Chassis configured with 24 Multi-Mode Ports, Single Power Supply
TLX-MSC-S00024	TLX24 Matrix Switch Chassis configured with 24 Single Mode (10km) Ports, Single Power Supply
TLX-MSC-CM0024	TLX24 Matrix Switch Chassis configured with 12 CATx Ports & 12 Multi-Mode Ports, Single Power Supply
TLX-MSC-CS0024	TLX24 Matrix Switch Chassis configured with 12 CATx Ports & 12 Single Mode (10km) Ports, Single Power Supply
Cables Included	(1) AC Power Cable & (1) CAT 5, 4.5m (CBL000001-015FR) (1) 24" 1.0/2.3 to Female BNC Cables per Coaxial Port
<b>Spare Modules</b>	
TLX-MSM-P00024	TLX24 Matrix Switch Power Supply